## **Performance Data Sheet**





## **Low Iron Glass**

Low Iron Glass is an ultra-transparent glass with light transmittance more than 91%, It has the characteristics of low spontaneous break- ages, high purity, noble elegance and crowned as 'crystal prince' of the glass family.

## **Products Feature**

**High transmittance**: visible light transmittance near 92%, 6% higher than clear float glass.

**High aesthetics:** More beautiful than clear float glass, with a jewel-like blue edge.

Glass Thickness		Visible Light		T-4-1	UV	Shading	Winter U-Value
mm	inches	Transmittance (VLT)	Exterior Reflectance	Total Penetration	Penetration	Coefficient	Metric W/(M <sup>2</sup> x K)
5mm	3/16"	91.3%	8%	90%	71%	1.03	5.80
6mm	1/4"	91.1%	8%	90%	70%	1.03	5.70
10mm	3/8"	90.6%	8%	89%	66%	1.02	5.60
12mm	1/2"	90.4%	8%	88%	64%	1.01	5.50
19mm	3/4"	89.7%	8%	86%	59%	0.99	5.50

**Visible Light Transmittance (VLT):** The percentage of the visible spectrum (light) that is transmitted through the glass.

**Exterior Reflectance:** The percentage of the visible spectrum (light) that is reflected towards the exterior by the glass.

**Winter U- Value:** Measure of the insulating characteristics of the glass in which how much heat gain or loss occurs through the glass due to the difference of indoor and outdoor temperatures using NFRC winter nighttime environmental conditions of a cold outside temperatures and no sunlight.

Interglass cannot be held responsible for any deviation between the data introduced and the conditions on site. Technical specifications and other data are based on information available at the time of preparation of this document and are subject to change without notice. Data values were simulated using Optics 6 & used with Windows 5.2. The performance data is simulated, not actually measured.